	SFSF	FVFV	FSFS	FVFS	FSFV	SFVF
SFSF	∞	1068	511	774	832	632
FVFV	1079	∞	546	5893	5225	451
FSFS	556	705	∞	1014	742	2227
FVFS	793	6436	895	∞	2881	517
FSFV	788	4271	507	2354	∞	414
SFVF	678	535	2250	571	520	∞

Table 1: Number of events needed to disfavour the column model with resepct to the row model by factor of 0.001 for file jlmSUSY.dat assuming data to come from the row model.

	SFSF	FVFV	FSFS	FVFS	FSFV	SFVF
SFSF	∞	1017	204	1450	740	713
FVFV	1130	∞	405	3263	4480	1761
FSFS	281	552	∞	417	742	871
FVFS	1710	3250	346	∞	1268	2389
FSFV	765	4098	507	1205	∞	1805
SFVF	839	1810	752	2389	1904	∞

Table 2: Number of events needed to disfavour the column model with resepct to the row model by factor of 0.001 for file jlpSUSY.dat assuming data to come from the row model.

	SFSF	FVFV	FSFS	FVFS	FSFV	SFVF
SFSF	∞	60748	23	148	15575	66
FVFV	60358	∞	22	164	6856	62
FSFS	36	34	∞	16	39	266
FVFS	156	173	11	∞	130	24
FSFV	15630	6873	25	122	∞	76
SFVF	78	73	187	27	90	∞

Table 3: Number of events needed to disfavour the column model with resepct to the row model by factor of 0.001 for file llSUSY.dat assuming data to come from the row model.

	SFSF	FVFV	FSFS	FVFS	FSFV	SFVF
SFSF	∞	514	∞	1659	353	65
FVFV	387	∞	387	1404	7998	40
FSFS	∞	514	∞	1659	353	65
FVFS	1498	1810	1498	∞	882	49
FSFV	245	7404	245	636	∞	35
SFVF	73	51	73	58	48	∞

Table 4: Number of events needed to disfavour the column model with resepct to the row model by factor of 0.001 for file qlf1SUSY.dat assuming data to come from the row model.

	SFSF	FVFV	FSFS	FVFS	FSFV	SFVF
SFSF	∞	757	71	332	430	63
FVFV	846	∞	173	455	6203	67
FSFS	114	248	∞	128	353	47
FVFS	347	472	105	∞	350	186
FSFV	490	6386	245	339	∞	62
SFVF	73	81	52	214	74	∞

Table 5: Number of events needed to disfavour the column model with resepct to the row model by factor of 0.001 for file qlf2SUSY.dat assuming data to come from the row model.

	SFSF	FVFV	FSFS	FVFS	FSFV	SFVF
SFSF	∞	53	36	53	36	29
FVFV	37	∞	616	∞	616	301
FSFS	23	569	∞	569	∞	2341
FVFS	37	∞	616	∞	616	301
FSFV	23	569	∞	569	∞	2341
SFVF	18	277	2349	277	2349	∞

Table 6: Number of events needed to disfavour the column model with resepct to the row model by factor of 0.001 for file qln1SUSY.dat assuming data to come from the row model.

	SFSF	FVFV	FSFS	FVFS	FSFV	SFVF
SFSF	∞	53	36	53	36	29
FVFV	37	∞	616	∞	616	301
FSFS	23	569	∞	569	∞	2341
FVFS	37	∞	616	∞	616	301
FSFV	23	569	∞	569	∞	2341
SFVF	18	277	2350	277	2350	∞

Table 7: Number of events needed to disfavour the column model with resepct to the row model by factor of 0.001 for file qln2SUSY.dat assuming data to come from the row model.